










# Fusion - Technical information

*Tile collection performance based on industry standards.*

## Technical Information

	WATER ABSORPTION	ANSI / ISO - (%)	< 0.5%
	ABRASION RESISTANCE	ANSI / ISO	CLASS 1
	SCRATCH HARDNESS	ANSI / ISO - (Mohs)	N/A
	BREAKING STRENGTH	ANSI - (lbf) ISO - (N)	>150 >650
	SHADE VARIATION		V3
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	GLOSSY N/A GLOSSY N/A
	CHEMICAL RESISTANCE	ANSI / ISO	CLASS A
	STAIN RESISTANCE	ANSI / ISO	CLASS A / CLASS 5
	FROST RESISTANCE	ANSI / ISO	PASS

Test values are based on ANSI standards according to: ANSI A137.2 Variances in test values can occur in different production lots.

## Usage recommendations

*Anatolia's recommendations for suitable applications.*

### Usage Recommendations\*

GLOSSY GLASS

APPLICATION		WALL	FLOOR
INTERIOR	RESIDENTIAL	•	
	COMMERCIAL	•	
	HEAVY COMMERCIAL		
EXTERIOR	RESIDENTIAL / COMMERCIAL	•	

\* These recommendations are not defined by ANSI/ISO standards.